

Micro Character Inkjet Printer DAYSJET®1760

It is designed to print clear marks in the limited space of the product

DAYSJET 1760 to provide customers with excellent jet printing quality, minimum height of 0.8mm, the fastest speed up to 280m/min. Stable, efficient, and can use more special ink, very suitable for use in electronics, cable and other fields.

- Modular system design for more stable operation.
- Simplified editing, parameter settings, and logo backup.
- Ink/makeup addition is more convenient and fast.
- Automatic cleaning on/off, even if parked for a long time, without the need for human intervention.
- Power outage protection function, even if there is a sudden power outage, ink will not overflow from the nozzle.
- Maintenance reminder
- Information and images can be accessed and accessed via USB.
- RS232 communication interface*
- Stable use of various inks, including universal ink, high adhesion ink, yellow ink, alcohol resistant ink, anti migration ink, high-temperature ink, invisible ink, edible ink, etc.



Parameter Table

Font size

Single: 5X5,5X7,7X9,9X12,10X16,16X24, 24X32

Double: 5X5,5X7,7X9,9X12

3Line: 5X5,5X7,7X9

4Line: 5X5,5X7

5Line: 5X5

Max. speed: 280m/minute

Nozzle 36U

Barcode 39、 128、 EN8、 EN13

DataMatrix

10X10,12X12,14X14,16X16, 21X21,29X29

Font height

The selection range is 2mm to 10mm, and the specific height depends on the font size.

Printing distance

Optimal distance:12mm


Range: 5-15mm

display screen

10.1-inch touch screen

Language and Interface

Multiple languages



Due to product improvements, increased performance parameters, and changes in appearance, we do not inform you separately. For details, please contact DAYSJET company.

Information storage

100 pieces, unrestricted when using USB storage

Protection level

IP55 stainless steel chassis

Nozzle head

Diameter: 42 millimeters Length: 248 millimeters

Laryngeal tube

Length: 2.5 meters

Ink and make up containers

Ink cartridge 750ml, make up 750ml

Temperature/humidity range

32 ° F to 122 ° F (0 ° C to 50 ° C)

0% to 90% RH non condensing

Electrical requirements

Input: 100-240vac 2.0A 50/60hz

Weight is approximately 21KG

Options

Host bracket, condenser, encoder, positive pressure air pump

Chongqing Daysjet Technology Co.,Ltd

Address: No.105 Yunhan Avenue,Beibei

District,chongqing,P.R.China

Tel: 023-67516665 400-887-9625

Fax: 023-67537803

www.daysjet.com.cn

Printing Speed (meter/minute)

	DAYSJET1770	DAYSJET1830PLUS	DAYSJET1760	DAYSJET1850
Single 5x5	396	396	280	396
Single 7x5	283	283	140	283
Single 9x7	110* (210)	110	110	110* (210)
Single 12x9	83* (140)	83	83	83* (140)
Single 16x11	61* (91)	61	61	61* (91)
Single 24x16	28* (50)	28	28	28* (50)
Single 32x25	15* (27)	15	15	15* (27)
Double 5x5	90* (180)	90	90	90* (180)
Double 7x5	66* (102)	66	66	66* (102)
Double 9x7	35* (67)	35	35	35* (67)
Double 12x9	19* (42)	19	19	19* (42)
Double 16x11	15* (26)	15	15	15* (26)
3 Line 5x5	38* (78)	38	38	38* (78)
3 Line 7x5	28* (53)	28	28	28* (53)
3 Line 9x7	17* (32)	17	17	17* (32)
4 Line 5x5	28* (53)	28	28	28* (53)
4 Line 7x5	15* (28)	15	15	15* (28)
5 Line 5x5	17* (32)	17	17	17* (32)

Note: 1. The speed test standard in the table is calculated based on a column spacing of 0.412mm. 2. With * for upgradable speed